

Ensto Beta heaters

With connection box or plug

Beta heaters can be installed in both dry and damp areas (IP21). The heaters also have a low surface temperature due to the X-shaped heating element. The heaters can be wall mounted or free standing (with separate feet).

BETA-EB

- > Connection box
- > RAL9010 colour
- > Extremely accurate and completely silent intelligent thermostat, accuracy +/-0.1°C
- > Fast reaction to temperature changes, which helps to increase comfort and ensures an even room temperature
- > The heater's surface temperature is low thanks to the intelligent thermostat
- > Manage intelligent functions with the Ensto Heat Control App
- > Standby consumption <0.3W

BETA-MP

- > Mechanical thermostat and plug
- > RAL9010 colour
- > Accurate temperature control with +/-0.5°C thermostat accuracy
- > A mechanical thermostat is better able to withstand network disturbances and is therefore suitable for use in cottages etc.

Ensto Beta heaters with intelligent thermostat and connection box

Beta heaters meet the Ecodesign requirements. The new heaters are equipped with intelligent thermostats (6 - 30°C) that can be controlled manually or with the Ensto Heat Control App (Android and iOS). The Ensto Heat Control application permits calendar control, boost and holiday function, and also the monitoring of heating consumption. Nominal voltage 230 V + 10%, -15%. Protection class IP21. Height of the heater is 389mm.

Old product code Old GTIN	New product code New GTIN	Description	Pkg./Pallet	
EPHBE02B 6418677635359	BETA2-BT-EB 6438100339401	250 W, 389x451 mm	1	40
EPHBE05B 6418677632020	BETA5-BT-EB 6438100339357	500 W, 389x585 mm	1	30
EPHBE07B 6418677632037	BETA7-BT-EB 6438100339364	750 W, 389x719 mm	1	30
EPHBE10B 6418677632044	BETA10-BT-EB 6438100339319	1000 W, 389x853 mm	1	20
EPHBE15B 6418677632051	BETA15-BT-EB 6438100339326	1500 W, 389x1121 mm	1	20
EPHBE20B 6418677632068	BETA20-BT-EB 6438100339340	2000 W, 389x1523 mm	1	26



BETA2-BT-EB

Portable Ensto Beta heaters with mechanical thermostat and Euro plug

Portable Beta heaters meet the Ecodesign requirements. Portable heaters are equipped with mechanical thermostats (6 - 36°C), Euro plug and heater legs. The accuracy of the thermostat is +/- 0.5°C. Thanks to the control wheel and a simple scale, adjusting the temperature is easy. Nominal voltage 230 V +10%, -15%. Protection class IP21. Height of the heater with legs is 460 mm.

Old product code Old GTIN	New product code New GTIN	Description	Pkg./Pallet	
EPHBM02P 6418677635786	BETA2-MP 6438100339395	250 W, 389x451 mm	1	40
EPHBM05P 6418677631832	BETA5-MP 6438100339418	500 W, 389x585 mm	1	30
EPHBM07P 6418677631849	BETA7-MP 6438100339425	750 W, 389x719 mm	1	30
EPHBM10P 6418677631856	BETA10-MP 6438100339371	1000 W, 389x853 mm	1	20
EPHBM15P 6418677631863	BETA15-MP 6438100339388	1500 W, 389x1121 mm	1	20
EPHBM20P 6418677631870	BETA20-MP 6438100339401	2000 W, 389x1523 mm	1	26



BETA2-MP

