


# ENSTO

KB241.12

Terminal strip

Code	KB241.12
GTIN	6418677106439
ENumber	
Name	Terminal strip Ensto Clampo 12-pole, wire protector
Description	Terminal block with flat base. Mounting hole $\varnothing$ 3.5 mm. Terminal screw M 3. Terminal block can be ordered precut to desired number of poles. On request individual pole positions can be marked with desired markings. To order imprinting please specify the characters on your order. Turret or ledge marking available.
Vendor	Ensto Finland Oy 



## Technical specification

### Technical specification

UL Cat.No.: 241.12SP-AK

### Dimensions

Weight: 33.0 g  
 Conductor cross-section: 4 mm<sup>2</sup>  
 Dimensions l x w x h: 117x22,2x15,8  
 Diameter of mounting hole: 3.5 mm

### Temperatures

Max. operating temperature: +100 °C

### Electrical values

CSA: 241-12SP  
 CSA Rated current: 30 A  
 CSA Rated voltage: 300 V

CSA Wire range: 18-12 AWG

## Materials

Material: Polyamide 6

## Features

Number of poles: 12

## Mechanical

Tightening torque: 0.6 Nm

## Certificates

UL File no.: E103245

## Ratings

Rated voltage: 450 V

ETIM 7: EC001284 Single- and multi-pole terminal strip

## ETIM

---

### ETIM

Length: 117 mm

Closing plate required: false

Material insulation body: Thermoplastic

Rated voltage: 450 V

Width/grid dimension: 22 mm

Mounting method: Direct mounting

Number of poles: 12

Colour: White

Type of electrical connection 1: Screw connection

Number of clamp positions per pole: 2

Height at lowest possible mounting height: 16 mm

Operation temperature: 80 °C

Connectable conductor cross section fine-strand with cable end sleeve: 1.5 ... 4 mm<sup>2</sup>

Connectable conductor cross section solid-core: 1.5 ... 4 mm<sup>2</sup>

Connectable conductor cross section fine-strand without cable end sleeve: 1.5 ... 4 mm<sup>2</sup>

Explosion-tested version 'Ex e': false

Connectable conductor cross section multi-wired: 1.5 ... 4 mm<sup>2</sup>

Inflammability class of insulation material acc. with UL94: V2

Rated current I<sub>n</sub>: 30 A

Transparent: true

Type of electrical connection 2: Screw connection

Connection position: Sideways

Drill hole distance centrally: 10 mm

## Packaging

---

### Default package

Unit: PCS  
Size: 250  
Length: 385 mm  
Width: 260 mm  
Height: 130 mm  
Weight (net): 8.25 kg  
Weight (brt): 8.5 kg  
Volume: 13.013

### Pallet package

Unit: PCS  
Size: 15750  
Length: 1200 mm  
Width: 800 mm  
Height: 1060 mm  
Weight (brt): 560.5 kg  
Volume: 1017.6

