

ENSTO

PRODUCT SPECIFICATION

5.3.2019



6418677681257

NCK5A.G

Coupler accessory

Code	NCK5A.G
GTIN	6418677681257
ENumber	
Name	Coupler accessory EnstoNet Grey
Description	
Vendor	Ensto Finland Oy
	

Technical specification

Dimensions

Weight: 12 g

Temperatures

Max. operating temperature: +70 °C
 Min. installation temperature: +5 °C
 Min. operating temperature: -30 °C (without mechanical stress)

Colors

Color: Grey

Ratings

Rated voltage: 250 V
 Flammability rating: UL 94 V-2
 Rated current: 20 A
 ETIM 7: EC002560 Plug-in connector for plug-in building installation

ETIM

ETIM

Rated voltage: 400 V
 Length: 36 mm
 With strain relief: true

Mechanical coding:	true
Pole codification:	3, N, PE, 2, 1
Colour coding/contact insert:	Grey
Material housing:	Polyamide (PA)
Rated current:	20 A
Width:	48 mm
Locking mechanism:	Integrated in plug-in connector
Connection type:	Screw connection
Halogen free:	true
Contact material:	CuZn
Number of poles:	5
Number of connections per pole:	1
Max. continuous temperature resistance strain relief:	70 °C
Pollution degree:	2
Surface finish contacts:	Silver-plated
Degree of protection (IP):	IP20
Height:	13 mm
Max. continuous temperature resistance contact part:	70 °C
Connection cross section (solid-core):	0.75 ... 4 mm ²
Connection cross section (fine-strand):	0.75 ... 4 mm ²
Model:	Plug
Rated surge voltage:	4 kV

Packaging

Default package

Unit:	PCS
Size:	100
Length:	220 mm
Width:	220 mm
Height:	125 mm
Weight (brt):	1.336 kg
Volume:	6.05

Pallet package

Unit:	PCS
Size:	12500