

Installation coupler accessories

Three-pole blanking cap

When EnstoNet installation couplers are installed in easily accessible spaces, the exposed socket couplers must be protected with a separate blanking cap. The NK3C.W is suitable for use with three-pole socket couplers.

Product code	GTIN	Description	Weight	Package
NK3C.W	6418677113963	White	0.2 g	100/1000



Five-pole blanking cap

When EnstoNet installation couplers are installed in easily accessible spaces, the exposed socket couplers must be protected with a separate blanking cap. The NK5C.W is suitable for use with five-pole socket couplers.

Product code	GTIN	Description	Weight	Package
NK5C.W	6418677700736	White	0.2 g	100/1000



Three-pole intermediate coupler

With the intermediate coupler luminaires equipped with installation couplers can be joined together to form a long lighting fixture.

Product code	GTIN	Description	Weight	Package
NAK3A.W	6418677113833	White	7.5 g	100/1000



Five-pole intermediate coupler

With the five-pole intermediate coupler, luminaires and other devices with side flanges can be connected to each other without an extension cable.

Product code	GTIN	Description	Weight	Package
NAK5A.W	6418677681240	White	12 g	100
NCK5A.G	6418677681257	Grey	12 g	100



Mounting pad

The NKB.W mounting pad is suitable for mounting to a DIN 35 rail or a surface with screws.

Product code	GTIN	Description	Weight	Package
NKB.W	6418677114243	White	11.3 g	100/1000
NKB.B	1935317	Black	11.3 g	100/1000



Safety device for the locking latches of three-pole couplers

When EnstoNet installation couplers are installed in easily accessible spaces, the couplers must be secured in such a manner that they can only be loosened with a tool. The locking device is placed over the locking latches of the couplers connected to each other to prevent them from being disconnected without a tool.

Product code	GTIN	Description	Weight	Package
NK3FH.W	6418677116605	White	1.9 g	100/1000



Safety device for the locking latches of five-pole couplers

When EnstoNet installation couplers are installed in easily accessible spaces, the couplers must be secured in such a manner that they can only be loosened with a tool. The locking device is placed over the locking latches of the couplers connected to each other to prevent them from being disconnected without a tool.

Product code	GTIN	Description	Weight	Package
NK5FH.W	6418677116612	White	3 g	100/1000

