

ENSTO

PRODUCT SPECIFICATION

2/28/2019



6418677688522

XLAD3F

Distribution block

Code	XLAD3F
GTIN	6418677688522
Name	Distribution block EnstoNet XL 3-pole 32 A, fused 10 A, switch, power
Description	Fused T-distributors have a 2-pole switch (N, L) with a 5 x 20 mm fuse. Fused T-distributors come provided with 10 A fuse. The fuse drawer has space for a spare fuse and, if needed the fuse holder can be padlocked into an open position for secured isolation. The fused T-distributors also comes with a switch. The switch indicates if the power is on in the downwards going outlet. The switch is lit and has an O/I indicator.
Vendor	Ensto Finland Oy



Technical specification

Dimensions

Dimensions l x w x h: 108 x 146 x 36

Temperatures

Max. operating temperature: 70 °C

Min. installation temperature: 5 °C

Certificates

Standards: EN 61535

Ratings

Rated voltage: 250 V

Degree of protection: IP20

Flammability rating: V-2

Rated current: 32 A

ETIM 7: EC002567 Compact distributor for plug-in building installation

ETIM

ETIM

Number of inputs:	1
Rated voltage:	250 V
Halogen free:	true
Length:	108 mm
Mechanical coding:	true
Pole codification:	L, N, PE
Colour coding/contact insert:	Black
Material housing:	Other
Number of poles:	3
Width:	146 mm
Locking mechanism:	Integrated in plug-in connector
Mounting possibility:	Integrated
Number of outputs:	2
Type of integrated switching:	Switch off
Contact material:	CuZn
Degree of protection (IP):	IP20
Max. continuous temperature resistance strain relief:	70 °C
Pollution degree:	2
Type of distributor:	Switching distributor
Surface finish contacts:	Silver-plated
Rated current:	32 A
Height:	59 mm
Max. continuous temperature resistance contact part:	70 °C
Rated surge voltage:	4 kV

Packaging

Default package

Unit:	PCS
Size:	15
Length:	220 mm
Width:	220 mm
Height:	175 mm
Weight (net):	2.7 kg
Weight (brt):	2.857 kg
Volume:	8.47

Pallet package

Unit:	PCS
-------	-----

Size:	1125
Length:	1200 mm
Width:	800 mm
Height:	1025 mm
Weight (brt):	239.275 kg
Volume:	984