

ENSTO

PRODUCT SPECIFICATION

2/28/2019



6418677688430

XLAD53L1

Distribution block

| | |
|-------------|--|
| Code | XLAD53L1 |
| GTIN | 6418677688430 |
| Name | Distribution block EnstoNet XL 5-pole 25 A, 3-phase cont. L1 out |
| Description | T-distributors have one input and two outputs. The input is always located on the left side when looking at the connector mounted. The input is always connected to a female socket coupler and the outputs to male plug couplers. The T-distributor can be fixed to a wall or ceiling using max. Ø 5mm flat head screws or with cable ties. |
| Vendor | Ensto Finland Oy |



Technical specification

Dimensions

Dimensions l x w x h: 108 x 146 x 36

Temperatures

Max. operating temperature: 70 °C

Min. installation temperature: 5 °C

Certificates

Standards: EN 61535

Ratings

Rated voltage: 250 ... 400 V

Degree of protection: IP20

Flammability rating: V-2

Rated current: 25 A

ETIM 7: EC002567 Compact distributor for plug-in building installation

ETIM

ETIM

| | |
|---|---------------------------------|
| Number of inputs: | 1 |
| Length: | 108 mm |
| Surface finish contacts: | Silver-plated |
| Mechanical coding: | true |
| Rated voltage: | 400 V |
| Colour coding/contact insert: | Black |
| Material housing: | Other |
| Width: | 146 mm |
| Locking mechanism: | Integrated in plug-in connector |
| Mounting possibility: | Integrated |
| Number of outputs: | 2 |
| Halogen free: | true |
| Contact material: | CuZn |
| Degree of protection (IP): | IP20 |
| Max. continuous temperature resistance strain relief: | 70 °C |
| Pollution degree: | 2 |
| Type of distributor: | T-distributor |
| Rated current: | 25 A |
| Height: | 37 mm |
| Max. continuous temperature resistance contact part: | 70 °C |
| Phase pickup: | L1 |
| Rated surge voltage: | 4 kV |

Packaging

Default package

| | |
|---------------|----------|
| Unit: | PCS |
| Size: | 20 |
| Length: | 220 mm |
| Width: | 220 mm |
| Height: | 175 mm |
| Weight (net): | 2.9 kg |
| Weight (brt): | 3.057 kg |
| Volume: | 8.47 |

Pallet package

| | |
|---------|---------|
| Unit: | PCS |
| Size: | 1500 |
| Length: | 1200 mm |
| Width: | 800 mm |
| Height: | 1025 mm |

| | |
|---------------|------------|
| Weight (brt): | 254.275 kg |
| Volume: | 984 |