

# ENSTO

**PRODUCT SPECIFICATION**

2/28/2019



6418677688447

XLAD53L2

Distribution block

Code	XLAD53L2
GTIN	6418677688447
Name	Distribution block EnstoNet XL 5-pole 25 A, 3-phase cont. L2 out
Description	T-distributors have one input and two outputs. The input is always located on the left side when looking at the connector mounted. The input is always connected to a female socket coupler and the outputs to male plug couplers. The T-distributor can be fixed to a wall or ceiling using max. Ø 5mm flat head screws or with cable ties.
Vendor	Ensto Finland Oy



## Technical specification

### Dimensions

Dimensions l x w x h: 108 x 146 x 36

### Temperatures

Max. operating temperature: 70 °C

Min. installation temperature: 5 °C

### Certificates

Standards: EN 61535

### Ratings

Rated voltage: 250 ... 400 V

Degree of protection: IP20

Flammability rating: V-2

Rated current: 25 A

ETIM 7: EC002567 Compact distributor for plug-in building installation

## ETIM

---

### ETIM

Number of inputs:	1
Length:	108 mm
Surface finish contacts:	Silver-plated
Mechanical coding:	true
Rated voltage:	400 V
Colour coding/contact insert:	Black
Material housing:	Other
Width:	146 mm
Locking mechanism:	Integrated in plug-in connector
Mounting possibility:	Integrated
Number of outputs:	2
Halogen free:	true
Contact material:	CuZn
Degree of protection (IP):	IP20
Max. continuous temperature resistance strain relief:	70 °C
Pollution degree:	2
Type of distributor:	T-distributor
Rated current:	25 A
Height:	37 mm
Max. continuous temperature resistance contact part:	70 °C
Phase pickup:	L2
Rated surge voltage:	4 kV

## Packaging

---

### Default package

Unit:	PCS
Size:	20
Length:	220 mm
Width:	220 mm
Height:	175 mm
Weight (net):	2.9 kg
Weight (brt):	3.057 kg
Volume:	8.47

### Pallet package

Unit:	PCS
Size:	1500
Length:	1200 mm
Width:	800 mm
Height:	1025 mm

Weight (brt):	254.275 kg
Volume:	984