

# ENSTO

**PRODUCT SPECIFICATION**

2/28/2019



6418677688553

XLCD5F

Distribution block

|             |  |
|-------------|--|
| Code        | XLCD5F   |
| GTIN        | 6418677688553  |
| Name        | Distribution block EnstoNet XL<br>5-pole 25 A, fused 10 A, switch, BUS   |
| Description | Fused T-distributors have a 2-pole switch (N, L) with a 5 x 20 mm fuse. Fused T-distributors come provided with 10 A fuse. The fuse drawer has space for a spare fuse and, if needed the fuse holder can be padlocked into an open position for secured isolation. The fused T-distributors also comes with a switch. The switch indicates if the power is on in the downwards going outlet. The switch is lit and has an O/I indicator. |
| Vendor      | Ensto Finland Oy   |



## Technical specification

### Dimensions

Dimensions l x w x h: 108 x 146 x 36

### Temperatures

Max. operating temperature: 70 °C

Min. installation temperature: 5 °C

### Certificates

Standards: EN 61535

### Ratings

Rated voltage: 250 ... 400 V

Degree of protection: IP20

Flammability rating: V-2

Rated current: 25 A

**ETIM 7:** EC002567 Compact distributor for plug-in building installation

## ETIM

---

### ETIM

|   |                                 |
|---|---------------------------------|
| Number of inputs:                                     | 1                               |
| Length:   | 108 mm                          |
| Halogen free:   | true                            |
| Surface finish contacts:                              | Silver-plated                   |
| Mechanical coding:                                    | true                            |
| Rated voltage:  | 400 V                           |
| Colour coding/contact insert:                         | Grey                            |
| Material housing:                                     | Other                           |
| Number of poles:                                      | 5                               |
| Width:  | 146 mm                          |
| Locking mechanism:                                    | Integrated in plug-in connector |
| Mounting possibility:                                 | Integrated                      |
| Number of outputs:                                    | 2                               |
| Type of integrated switching:                         | Switch off                      |
| Contact material:                                     | CuZn                            |
| Degree of protection (IP):                            | IP20                            |
| Max. continuous temperature resistance strain relief: | 70 °C                           |
| Pollution degree:                                     | 2                               |
| Type of distributor:                                  | Switching distributor           |
| Rated current:  | 25 A                            |
| Height:   | 59 mm                           |
| Max. continuous temperature resistance contact part:  | 70 °C                           |
| Rated surge voltage:                                  | 4 kV                            |

## Packaging

---

### Default package

|               |          |
|---------------|----------|
| Unit:         | PCS      |
| Size:         | 15       |
| Length:       | 220 mm   |
| Width:        | 220 mm   |
| Height:       | 175 mm   |
| Weight (net): | 2.55 kg  |
| Weight (brt): | 2.707 kg |
| Volume:       | 8.47     |

### Pallet package

|       |      |
|-------|------|
| Unit: | PCS  |
| Size: | 1125 |

|               |            |
|---------------|------------|
| Length:       | 1200 mm    |
| Width:        | 800 mm     |
| Height:       | 1025 mm    |
| Weight (brt): | 228.025 kg |
| Volume:       | 984        |