

ENSTO

PRODUCT SPECIFICATION

2/28/2019



6418677688478

XLPD5

Distribution block

Code	XLPD5
GTIN	6418677688478
Name	Distribution block EnstoNet XL 5-pole, 25 A, 2nd power
Description	T-distributors have one input and two outputs. The input is always located on the left side when looking at the connector mounted. The input is always connected to a female socket coupler and the outputs to male plug couplers. The T-distributor can be fixed to a wall or ceiling using max. Ø 5mm flat head screws or with cable ties.
Vendor	Ensto Finland Oy



Technical specification

Dimensions

Dimensions l x w x h: 108 x 146 x 36

Temperatures

Max. operating temperature: 70 °C

Min. installation temperature: 5 °C

Certificates

Standards: EN 61535

Ratings

Rated voltage: 250 ... 400 V

Degree of protection: IP20

Flammability rating: V-2

Rated current: 25 A

ETIM 7: EC002567 Compact distributor for plug-in building installation

ETIM

ETIM

Number of inputs:	1
Rated voltage:	400 V
Length:	108 mm
Mechanical coding:	true
Pole codification:	3, N, PE, 2, 1
Colour coding/contact insert:	Red
Material housing:	Other
Number of poles:	5
Width:	146 mm
Locking mechanism:	Integrated in plug-in connector
Mounting possibility:	Integrated
Number of outputs:	2
Halogen free:	true
Contact material:	CuZn
Degree of protection (IP):	IP20
Max. continuous temperature resistance strain relief:	70 °C
Pollution degree:	2
Type of distributor:	T-distributor
Surface finish contacts:	Silver-plated
Rated current:	25 A
Height:	37 mm
Max. continuous temperature resistance contact part:	70 °C
Rated surge voltage:	4 kV

Packaging

Default package

Unit:	PCS
Size:	20
Length:	220 mm
Width:	220 mm
Height:	175 mm
Weight (net):	3.04 kg
Weight (brt):	3.197 kg
Volume:	8.47

Pallet package

Unit:	PCS
Size:	1500
Length:	1200 mm
Width:	800 mm

Height:	1025 mm
Weight (brt):	264.775 kg
Volume:	984