

# Broadband Coax

## CATV Cables

### Series 6

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

**Series 6 • 18 AWG** Solid .040" Bare Copper-covered Steel Conductor • Duobond® IV Quad Shield (60% and 40% Coverage)

**Gas-injected Foam Polyethylene Insulation • Polyethylene Jacket with CoreGuard® (Black or Orange)**

Burial 80°C	1190A	—	1000	304.8	31.0	14.1	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.180	4.57	Duobond IV* 60% + 40% Aluminum Braids 4.8Ω/M' 15.7Ω/km	.298	7.57	75	83%	16.2	53.1	See Chart on page 6.92		



CoreGuard®

**Series 6 • 18 AWG** Solid .040" Bare Copper-covered Steel Conductor • Duofoil® (100% Coverage) + TC Braid Shield (95% Coverage)

**Plenum • Foam FEP Insulation • Black FEP Jacket**

200°C	89120	NEC: CATVP CMP CEC: CMP FT6	500	152.4	21.5	9.8	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.170	4.32	Duofoil 95% TC Braid 1.7Ω/M' 5.6Ω/km	.234	5.94	75	82%	16.5	54.1	1	.3	1.0
			1000	304.8	46.0	20.9											10	.7	2.2



**Plenum • Foam FEP Insulation • Black Fluorocopolymer Jacket**

150°C	87120	NEC: CATVP CMP CEC: CMP FT6, CXC FT4	500	152.4	20.5	9.3	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.170	4.32	Duofoil 95% TC Braid 1.7Ω/M' 5.6Ω/km	.234	5.94	75	82%	16.5	54.1	1	.3	1.0
			1000	304.8	45.0	20.4											10	.7	2.2



**Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket**

75°C	82120	NEC: CATVP CMP CEC: CMP FT6	1000	304.8	44.0	20.0	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.170	4.32	Duofoil 95% TC Braid 1.7Ω/M' 5.6Ω/km	.234	5.94	75	82%	16.5	54.1	1	.3	1.0
																	10	.7	2.2



**Series 6 • 18 AWG** Solid .040" BCCS Conductor • Duofoil (100% Coverage) + TC Braid Shield (60% and 40% Coverage)

**Plenum • Foam FEP Insulation • Snow Beige FEP Jacket**

200°C	1152A	NEC: CMP CEC: CMP FT6	500	152.4	27.5	12.5	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.170	4.32	(2) Duofoil Shields + (2) TC Braids 1.8Ω/M' 5.9Ω/km	.273	6.93	75	82%	16.5	54.1	1	.3	1.0
			1000	304.8	53.0	24.1											10	.7	2.2



BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

\*Duobond IV = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage) + aluminum braid (46% coverage).