

For more Information  
please call

1-800-Belden1



### Description:

18 AWG stranded (7x26) tinned copper conductors, flame-retardant polyolefin insulation, overall Beldfoil® (100% coverage) plus a tinned copper braid shield (55% coverage), sunlight-resistant PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	18	7x26	TC - Tinned Copper	1.1684

Total Number of Conductors: 2

#### Insulation

##### Insulation Material:

Insulation Material	Dia. (mm)
FRPO - Flame Retardant Polyolefin	4.1656

#### Outer Shield

##### Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	55

##### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Shield Drain Wire Diameter: .038

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 11.684 mm

#### Pair

##### Pair Color Code Chart:

Number	Color
1	Natural
2	Blue

### Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

UL Temperature Rating: 75°C Dry

Bulk Cable Weight: 133.343 Kg/Km

Max. Recommended Pulling Tension: 413.683 N

Min. Bend Radius/Minor Axis: 114.300 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG, PLTC, ITC, TC
CEC/C(UL) Specification:	CMG
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/13/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	UL1685 FT4 Loading
C(UL) Flame Test:	FT1, FT4

### Suitability

Sunlight Resistance:	Yes
----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Surface Printing (Overall)

## Electrical Characteristics (Overall)

### Nominal Input Impedance:

Freq. (MHz)	Impedance (Ohm)
1.000	124.000

### Nom. Inductance:

Inductance (µH/m)
0.59058

### Nom. Mutual Capacitance:

Capacitance (pF/m)
40.3563

### Nominal Velocity of Propagation:

VP (%)
64.5

### Nominal Delay:

Delay (ns/m)
5.18398

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
22.6389

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
9.28523

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	1.11554
10	3.51067
50	7.84159

METRIC MEASUREMENT VERSION

## 3074F Twinax - DataTray® 600V Twinaxial Cable

100	11.0898
200	15.6832
400	22.1796

### Max. Operating Voltage - UL:

<b>Voltage</b>
600 V RMS (NEC Type TC)

### Notes (Overall)

**Notes:** CPE Jacket Optional.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3074F C551000	305 MT	53.524 KG	BLUE, CAIRO	C	#18 FSPR FRPP SH PVC
3074F C552500	762 MT	136.078 KG	BLUE, CAIRO	C	#18 FSPR FRPP SH PVC
3074F C55500	152 MT	28.350 KG	BLUE, CAIRO	C	#18 FSPR FRPP SH PVC
3074F C555000	1,524 MT	281.229 KG	BLUE, CAIRO	C N	#18 FS PR FRPP SH PVC

#### Notes:

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 1    Revision Date: 12-12-2008

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.