

Security and Alarm Cables

Commercial Applications Unshielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

12 AWG • Stranded (19x25) 2.4 mm Bare Copper • Numbered and Color Coded • Rip Cord

Polyethylene Insulation • Grey PVC Jacket

300V 75°C	NEC: CL3R						2.36 mm 12 AWG (19x25) BC	0.107	2.72	Unshielded			
--------------	--------------	--	--	--	--	--	---------------------------------	-------	------	------------	--	--	--




5000UE	2 CDR	500 1000	152 305	29.1 57.1	13.2 25.9						0.268	6.81	Black, White
---------------	-------	-------------	------------	--------------	--------------	--	--	--	--	--	-------	------	--------------

Also available in Red for fire alarm (FPLR).

5001UE	3 CDR	1000	305	82.2	37.3						0.286	7.26	Black, White, Red
---------------	-------	------	-----	------	------	--	--	--	--	--	-------	------	-------------------

Polyethylene Insulation • Grey FRNC / LSNH Jacket

300V 75°C	IEC 60754-2						2.36 mm 12 AWG (19x25) BC	0.118	3.00	Unshielded			
--------------	-------------	--	--	--	--	--	---------------------------------	-------	------	------------	--	--	--



4000UE	2 CDR	328 1640	100 500	16.5 83.1	7.5 37.7						0.268	6.80	Black, White
---------------	-------	-------------	------------	--------------	-------------	--	--	--	--	--	-------	------	--------------

4001UE	3 CDR	1640	500	375.2	170.2						0.287	7.30	Black, White, Red
---------------	-------	------	-----	-------	-------	--	--	--	--	--	-------	------	-------------------

BC = Bare Copper • DCR = DC resistance