

Security and Alarm Cables

Commercial Applications Shielded




| De-scription | Part No. | UL NEC/ C(UL)CEC Type IEC | Standard Lengths | | Standard Unit Weight | | Conductor (Stranding) Diameter Nom. DCR | Nominal Insulation OD | | Shielding Material Nom. DCR | Nominal OD | | Color Code |
|--------------|----------|---------------------------|------------------|---|----------------------|----|---|-----------------------|----|-----------------------------|------------|----|------------|
| | | | ft. | m | lbs. | kg | | inch | mm | | inch | mm | |

16 AWG • Stranded (19x29) 1.5 mm Bare Copper • Beldfoil® Shield • 18 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket


| | | | | | | | | | | | | | |
|--------------|--------------------------------|--|--|--|--|--|---------------------------------|-------|------|---|--|--|--|
| 300V 75°C | NEC: CMR CEC: CMG FT4 | | | | | | 1.47 mm 16 AWG (19x29) BC | 0.068 | 1.72 | Overall Beldfoil® + Drain Wire (18 AWG TC) | | | |
|--------------|--------------------------------|--|--|--|--|--|---------------------------------|-------|------|---|--|--|--|



| | | | | | | | | | | | | | | |
|--------------------------|-------|--------|-------|------|------|--|--|--|--|--|-------|------|--------------------------|--|
| 5200FE | 2 CDR | U-500 | U-152 | 16.5 | 7.5 | | | | | | 0.188 | 4.78 | Black, Red | |
| | | 500 | 152 | 16.5 | 7.5 | | | | | | | | | |
| | | U-1000 | U-305 | 31.1 | 14.1 | | | | | | | | | |
| | | 1000 | 305 | 32.0 | 14.5 | | | | | | | | | |
| Also available in White. | | | | | | | | | | | | | | |
| 5201FE | 3 CDR | 500 | 152 | 21.6 | 9.8 | | | | | | 0.200 | 5.08 | Black, Red, White | |
| | | U-1000 | U-305 | 43.0 | 19.5 | | | | | | | | | |
| | | 1000 | 305 | 42.1 | 19.1 | | | | | | | | | |
| 5202FE | 4 CDR | 500 | 152 | 26.5 | 12.0 | | | | | | 0.220 | 5.59 | Black, Red, White, Green | |
| | | 1000 | 305 | 54.0 | 24.5 | | | | | | | | | |

Polyethylene Insulation • Grey FRNC/LSNH Jacket

| | | | | | | | | | | | | | |
|--------------|----------------|--|--|--|--|--|---------------------------------|-------|------|---|--|--|--|
| 300V 70°C | IEC 60754-2 | | | | | | 1.47 mm 16 AWG (19x29) BC | 0.077 | 1.95 | Overall Beldfoil® + Drain Wire (18 AWG TC) | | | |
|--------------|----------------|--|--|--|--|--|---------------------------------|-------|------|---|--|--|--|



| | | | | | | | | | | | | | |
|---------------|-------|------|-----|------|------|--|--|--|--|--|-------|------|--------------------------|
| 4200FE | 2 CDR | 328 | 100 | 9.7 | 4.4 | | | | | | 0.189 | 4.80 | Black, Red |
| | | 1640 | 500 | 48.1 | 21.8 | | | | | | | | |
| 4201FE | 3 CDR | 328 | 100 | 11.9 | 5.4 | | | | | | 0.201 | 5.10 | Black, Red, White |
| | | 1640 | 500 | 59.5 | 27.0 | | | | | | | | |
| 4202FE | 4 CDR | 328 | 100 | 15.2 | 6.9 | | | | | | 0.220 | 5.60 | Black, Red, White, Green |
| | | 1640 | 500 | 75.8 | 34.4 | | | | | | | | |

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance