

Security and Alarm Cables

Commercial Applications Unshielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

16 AWG • Stranded (19x29) 1.5 mm Bare Copper • Numbered and Color Coded • Rip Cord

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V
70°C
IEC 60754-2
1.47 mm
16 AWG
(19x29) BC
0.077 1.95 Unshielded




Rip Cord

4200UE	2 CDR	328 1640	100 500	7.5 37.3	3.4 16.9						0.185	4.70	Black, White
4201UE	3 CDR	328 1640	100 500	9.9 49.8	4.5 22.6						0.197	5.00	Black, White, Red
4202UE	4 CDR	328 1640	100 500	13.2 65.7	6.0 29.8						0.217	5.50	Black, White, Red, Green

14 AWG • Stranded (19x27) 1.9 mm Bare Copper • Numbered and Color Coded • Rip Cord

Polyethylene Insulation • Grey PVC Jacket

300V
75°C
NEC:
CMR
FPLR
CL3R
1.85 mm
14 AWG
(19x27) BC
0.087 2.21 Unshielded




Rip Cord

5100UE	2 CDR	500 U-1000 1000	152 U-305 305	20.1 37.9 40.1	9.1 17.2 18.2						0.234	5.94	Black, White	
Also available in Red for fire alarm (FPLR).														
5101UE	3 CDR	1000	305	56.2	25.5						0.249	6.32	Black, White, Red	
5102UE	4 CDR	500 1000	152 305	38.6 73.2	17.5 33.2						0.276	7.01	Black, White, Red, Green	

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V
70°C
IEC 60754-2
1.85 mm
14 AWG
(19x27) BC
0.099 2.52 Unshielded



Rip Cord

4100UE	2 CDR	328 1640	100 500	11.5 57.8	5.2 26.2						0.232	5.90	Black, White
4101UE	3 CDR	328 1640	100 500	15.4 76.9	7.0 34.9						0.248	6.30	Black, White, Red
4102UE	4 CDR	328 1640	100 500	20.5 103.0	9.3 46.7						0.276	7.00	Black, White, Red, Green

BC = Bare Copper • DCR = DC resistance