

Security and Alarm Cables

Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

16 AWG • Stranded (19x29) 1.5 mm Bare Copper • Beldfoil® Shield • 18 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket


300V 75°C	NEC: CMR CEC: CMG FT4						1.47 mm 16 AWG (19x29) BC	0.068	1.72	Overall Beldfoil® + Drain Wire (18 AWG TC)			
--------------	--------------------------------	--	--	--	--	--	---------------------------------	-------	------	---	--	--	--



5200FE	2 CDR	U-500 500	U-152 152	16.5 16.5	7.5 7.5						0.188	4.78	Black, Red
		U-1000 1000	U-305 305	31.1 32.0	14.1 14.5								
Also available in White.													
5201FE	3 CDR	500 U-1000 1000	152 U-305 305	21.6 43.0 42.1	9.8 19.5 19.1						0.200	5.08	Black, Red, White
5202FE	4 CDR	500 1000	152 305	26.5 54.0	12.0 24.5						0.220	5.59	Black, Red, White, Green

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V 70°C	IEC 60754-2						1.47 mm 16 AWG (19x29) BC	0.077	1.95	Overall Beldfoil® + Drain Wire (18 AWG TC)			
--------------	----------------	--	--	--	--	--	---------------------------------	-------	------	---	--	--	--



4200FE	2 CDR	328 1640	100 500	9.7 48.1	4.4 21.8						0.189	4.80	Black, Red
4201FE	3 CDR	328 1640	100 500	11.9 59.5	5.4 27.0						0.201	5.10	Black, Red, White
4202FE	4 CDR	328 1640	100 500	15.2 75.8	6.9 34.4						0.220	5.60	Black, Red, White, Green

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance