



Product: [439945](#)

CCTV plus Audio, Pan and Tilt CCTV Control

Product Description

CCTV plus Audio, Pan and Tilt CCTV Control, Coax RG-6, 18 AWG solid bare copper, foamed polyethylene core, 95% bare copper braid, LSZH jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	CCTV plus Audio, Pan and Tilt CCTV Control; Suitable for indoor, outdoor and Aerial use

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	Nominal Diameter	No. of Coax
Coax	18	Solid	BC - Bare Copper	1.02 mm	1
Twisted pair	18	Stranded 7xAWG26	BC - Bare Copper	1.17 mm	

Conductor Count:	1
------------------	---

Insulation

Element	Type	Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness	Color
Coax	Dielectric	FPE - Foamed Polyethylene	4.57 mm			
Twisted pair	Insulation	Polyethylene	1.7 mm	0.05 mm	0.25 mm	Black & Red

Inner Shield Material

Element	Type	Material	Coverage [%]
Coax	Braid	Bare copper	95 %

Outer Jacket Material

Element	Material	Nominal Diameter	Nominal Wall Thickness
Coax	LSZH / FRNC	6.8 mm	0.38 mm

Construction and Dimensions

OuterJacket1, Form:	Shotgun
OuterJacket1, Nominal Width:	12.7 mm

Electrical Characteristics

Conductor DCR

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
Coax	21 Ohm/km	10.2 Ohm/km
Twisted pair	21 Ohm/km	

Capacitance

Element	Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
Coax		53.4 pF/m
Twisted pair	78.7 pF/m	

Impedance

Element	Nominal Characteristic Impedance
Coax	75 Ohm

High Frequency (Nominal/Typical)

Element	Frequency [MHz]	Nom. Insertion Loss
Coax	1 MHz	0.56 dB/100m
	5 MHz	1.48 dB/100m
	10 MHz	2.1 dB/100m
	50 MHz	4.79 dB/100m
	100 MHz	6.89 dB/100m
	200 MHz	9.84 dB/100m
	400 MHz	14.1 dB/100m
	700 MHz	19 dB/100m
	900 MHz	22 dB/100m
	1000 MHz	23.3 dB/100m

Delay

Element	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
Coax	400 ns/ft	83 %

Voltage

Element	Voltage Rating [V]
Coax	300 V RMS
Twisted pair	300 V RMS

Temperature Range

Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

Mechanical Characteristics

Max Recommended Pulling Tension:	52 N
Min Bend Radius (W/o Pulling Strength):	34 mm
Min Setting Radius:	68 mm

Standards

RG Type:	6/U Type
----------	----------

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Part Number

Variants

Item #	Color	Length
439945.00100	Gray	100 m
439945.00500	Gray	500 m

History

Update and Revision:	Revision Number: 0.148 Revision Date: 02-14-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.