

Security and Alarm Cables

Commercial Applications Unshielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

22 AWG • Stranded (7x30) 0.8 mm Bare Copper • Numbered and Color Coded • Rip Cord

Polyethylene Insulation • Grey FRNC/LSNH Jacket

300V IEC 60754-2 0.76 mm 0.049 1.25 Unshielded see chart below
 70°C 22 AWG (7x30) BC



4500UE	2 CDR	328 1640	100 500	3.1 15.4	1.4 7.0						0.130	3.30	
4501UE	3 CDR	328 1640	100 500	3.1 15.4	1.4 7.0						0.130	3.30	
4502UE	4 CDR	328 1640	100 500	5.3 26.0	2.4 11.8						0.154	3.90	
4504UE	6 CDR	328 1640	100 500	7.3 36.2	3.3 16.4						0.177	4.50	
4506UE	8 CDR	328 1640	100 500	8.8 43.7	4.0 19.8						0.193	4.90	
4509UE	12 CDR	328 1640	100 500	13.4 66.8	6.1 30.3						0.232	5.90	

BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Grey
5	Brown	11	Pink
6	Blue	12	Tan