

4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI



For more Information
please call

1-800-Belden1



General Description:

12 GHz, 4K UHD Precision Video Cable, 75 Ohm, 16 AWG solid 0.051" silver-plated copper conductor, gas-injected foamed high-density polyethylene insulation, Duofoil® bonded to the core + tinned copper braid shield (95% coverage) plus Beldfoil® with shorting fold, PVC jacket.

Usage (Overall)

Suitable Applications: SMPTE 2082-1 12 Gb/s UHDTV, SMPTE 2081-1 6 Gb/s UHDTV, SMPTE 424M 3 Gb/s HD-SDI 1080p

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	16	Solid	SPC - Silver Plated Copper	1.295

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FHDPE - Foam High Density Polyethylene	5.715

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
1	Bonded Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100.000	Bonded to insulation
2		Braid	TC - Tinned Copper	95.000	
3	Bonded Beldfoil® with shorting fold	Tape	Polyester Tape-Aluminum Foil	100.000	Bonded to jacket

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 8.128 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +75°C

Bulk Cable Weight: 87.804 Kg/Km

Max. Recommended Pulling Tension: 493.750 N

Min. Bend Radius/Minor Axis: 82.550 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Series Type:	Series 7

Flame Test

UL Flame Test:	UL1666 Vertical Shaft
CSA Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only.
Suitability - Aerial:	Yes - Black only, when supported by messenger wire.
Suitability - Burial:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (µH/m)
0.299

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
50.856

Nominal Velocity of Propagation:

VP (%)
85.000

Nominal Delay:

Delay (ns/m)
3.937

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
13.124

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
6.234

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	0.853
3.580	1.411
5.000	1.641
6.000	1.706
7.000	1.805

4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI

10.000	2.067
12.000	2.165
25.000	2.887
55.000	3.970
67.500	4.298
71.500	4.397
88.500	4.823
100.000	5.053
135.000	5.742
143.000	5.873
180.000	6.496
270.000	7.874
360.000	9.056
540.000	11.188
720.000	12.993
750.000	13.288
1000.000	15.421
1500.000	19.128
2000.000	22.311
2250.000	23.787
3000.000	27.823
4500.000	34.975
6000.000	40.914
12000.000	63.815

Max. Operating Voltage - UL:

Voltage
300 V RMS

Other Electrical Characteristic 1:

Return Loss: Fixed bridge and termination.

Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	1600.000	23.000
1600.000	4500.000	21.000
4500.000	12000.000	15.000

Sweep Test

Sweep Testing:

Sweep tested 5 MHz to 12 GHz.

Notes (Overall)

Notes: Print legend includes sequential footage marks.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
4794R N3U1000	1,000 FT	60.000 LB	GREEN, MIL		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0021000	1,000 FT	60.000 LB	RED		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0031000	1,000 FT	60.000 LB	ORANGE		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0041000	1,000 FT	60.000 LB	YELLOW		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0061000	1,000 FT	60.000 LB	BLUE, LIGHT		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0071000	1,000 FT	60.000 LB	VIOLET		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0091000	1,000 FT	60.000 LB	WHITE	C	#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0101000	1,000 FT	60.000 LB	BLACK	C	#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0102500	2,500 FT	145.000 LB	BLACK	C Z	#16 LDPE/GIFHDLDPPE SH FRPVC

Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI

Revision Number: 4 Revision Date: 04-12-2017

© 2019 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).