

5000UP Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information
please call

1-800-Belden1



Description:

12 AWG bare high-conductivity ETP copper conductors, highly stranded for ultra flexibility, high-grade PVC insulation, PVC jacket with ripcord, sequential footage marking every two feet.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	12	65x30	Bare High-Conductivity ETP Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.508

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.4572

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Lay Length & Direction:

Length (mm)	Twists (twist/m)
101.5996	9.843

Overall Cabling Color Code Chart:

Color
Black
White

Overall Nominal Diameter: 7.671 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 87.804 Kg/Km

Max. Recommended Pulling Tension: 751.746 N

Min. Bend Radius/Minor Axis: 76.200 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

METRIC MEASUREMENT VERSION

5000UP Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

NEC/(UL) Specification:	CL3
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.52496

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
104.992

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
5.11836

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Current
26 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5000UP D151000	305 MT	29.030 KG	BLUE		2 #12 PVC FRPVC
5000UP D15500	152 MT	14.742 KG	BLUE	C	2 #12 PVC FRPVC
5000UP 0051000	305 MT	29.030 KG	GREEN, DARK	C	2 #12 PVC FRPVC
5000UP 0081000	305 MT	29.030 KG	GRAY		2 #12 PVC FRPVC
5000UP 008500	152 MT	14.742 KG	GRAY	C	2 #12 PVC FRPVC
5000UP 009U500	152 MT	14.061 KG	WHITE		2 #12 PVC FRPVC
5000UP 0091000	305 MT	29.030 KG	WHITE		2 #12 PVC FRPVC
5000UP 010U500	152 MT	14.061 KG	BLACK		2 #12 PVC FRPVC
5000UP 0101000	305 MT	29.030 KG	BLACK	C	2 #12 PVC FRPVC
5000UP 010500	152 MT	14.742 KG	BLACK		2 #12 PVC FRPVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

5000UP Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.