

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

For more Information
please call

1-800-Belden1



Description:

Coax:20 AWG solid BC cond., gas-injected foam HDPE insul., 95% BC braid shield, PVC jacket, cabled with(1) pair - 23 AWG solid BC conductor, PO insulation, PVC Jacket, and cabled with (2) conductors, 18 AWG (7x26) BC conductors, PP insulation,PVC jacket

Coax

Physical Characteristics

Conductor

AWG:

AWG	Stranding	Conductor Material	Dia. (mm)	# Conductors
20	Solid	BC - Bare Copper	0.813	1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected PHDPE - Foam High Density Polyethylene	3.683

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
5.766

Outer Jacket Color Code Chart:

Number	Color
Video	Black

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU CE Mark: Yes

RG Type: 59/U

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)

METRIC MEASUREMENT VERSION

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

75

Nom. Inductance:

Inductance (µH/m)
0.318

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
53.480

Nominal Velocity of Propagation:

VP (%)
83.000

Nominal Delay:

Delay (ns/m)
4.003

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
32.810

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
11.484

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	0.984
5.000	2.133
10.000	2.953
50.000	6.234
100.000	8.531
200.000	11.812
400.000	16.405
700.000	22.967
900.000	26.248
1000.000	27.889

Max. Operating Voltage - UL: 300 V RMS

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	23	Solid	BC - Bare Copper	0.584

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
PO - Polyolefin	1.041

Twisted Pair Color Code Chart:

Number	Color
1	Blue and White/Blue

Outer Shield

Outer Shield Material:

Type	Dia. (mm)
PVC - Polyvinyl Chloride	2.997

Outer Jacket

Outer Jacket Color Code Chart:

Number	Color
--------	-------

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

1	Blue
---	------

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

49.215

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

65.620

Max. Operating Voltage - Other:

Voltage

300 V RMS

Max. Recommended Current:

Current

2.4 Amps per conductor @ 25°C

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
2	18	7x26	BC - Bare Copper	1.194

Insulation

Insulation Material:

Insulation Material

PP - Polypropylene

Insulation Color Code Chart:

Number Color

1 Red

2 Black

Individual Shield

Outer Jacket

Outer Jacket Diameter:

Nom. Dia. (mm)

4.013

Outer Jacket Color Code Chart:

Number Color

1 White

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

70.542

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

21.327

Max. Operating Voltage - Other:

Voltage

300 V RMS

Physical Characteristics (Overall)

Conductor

Outer Jacket

Outer Jacket Material:

Outer Jacket Material

Unjacketed

Overall Cable

Overall Nominal Diameter: 10.439 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 89.292 Kg/Km

Max. Recommended Pulling Tension: 511.543 N

Min. Bend Radius/Minor Axis: 104.140 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 600PTZ

Notes (Overall)

Notes: RG59 CCTV + 1PR23 UTP + 2C 18 AWG CMR. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation. Banana Peel® US Patent 7049523.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

METRIC MEASUREMENT VERSION

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

500PTZ 0001000	305 MT	26.308 KG	NONE	C	1 RG59 + 1 UTP 23 + 2C18
----------------	--------	-----------	------	---	--------------------------

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 07-15-2008

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.