

502PTZ Composite - For PTZ Cameras: CCTV + Control + Power



For more Information
please call

1-800-Belden1



Description:

(1) coax-20 AWG solid BC cond., gas-injected foam HDPE insul., 95% BC braid shield, PVC jkt., cabled with (1) pair - 18 AWG stranded (19x30) BC cond., PO insul., Beldfoil® shield, PVC jkt., cabled with (2) cond.-18 AWG (7x26) BC cond., PP insul., PVC Jkt.

Coax

Physical Characteristics

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	Solid	BC - Bare Copper	0.813

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FHDPE - Foam High Density Polyethylene	3.683

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
5.766

Outer Jacket Color Code Chart:

Number	Color
Video	Black

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU CE Mark: Yes

RG Type: 59/U

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)

METRIC MEASUREMENT VERSION

502PTZ Composite - For PTZ Cameras: CCTV + Control + Power

75

Nom. Inductance:

Inductance (µH/m)
0.318

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
53.480

Nominal Velocity of Propagation:

VP (%)
83.000

Nominal Delay:

Delay (ns/m)
4.003

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
32.810

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
11.484

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	0.984
5.000	2.133
10.000	2.953
50.000	6.234
100.000	8.531
200.000	11.812
400.000	16.405
700.000	22.967
900.000	26.248
1000.000	27.889

Max. Operating Voltage - UL:

300 V RMS

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	18	19x30	BC - Bare Copper	1.118

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
PO - Polyolefin	2.032

Twisted Pair Color Code Chart:

Number	Color
1	Blue and White/Blue

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
5.563

Outer Jacket Color Code Chart:

Number	Color
1	Blue

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
144.364

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
85.306

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
21.327

Max. Operating Voltage - Other:

Voltage
300 V RMSI

Max. Recommended Current:

Description	Current
Data/Control	5.2 Amps

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
2	18	7x26	BC - Bare Copper	1.194

Insulation

Insulation Material:

Insulation Material
PP - Polypropylene

Insulation Color Code Chart:

Number	Color
1	Red
2	Black

Individual Shield

Outer Jacket

Outer Jacket Diameter:

Nom. Dia. (mm)
4.013

Outer Jacket Color Code Chart:

Number	Color
1	White

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
70.542

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
21.327

Max. Operating Voltage - Other:

Voltage
300 V RMS

Max. Recommended Current:

Current
5 Amps per conductor @ 25°C

Physical Characteristics (Overall)

Conductor

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

Overall Cable

Overall Nominal Diameter: 11.455 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 110.127 Kg/Km

Max. Recommended Pulling Tension: 622.748 N

Min. Bend Radius/Minor Axis: 114.300 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

502PTZ Composite - For PTZ Cameras: CCTV + Control + Power

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 602PTZ

Notes (Overall)

Notes: RG59 CCTV + 1 STP18 AWG Control Grade + 2C 18 AWG CMR. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation. Banana Peel® US PATENT 7049523.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
502PTZ 0001000	305 MT	40.370 KG	NONE		1 RG59 + 2C18 SH + 2C18
502PTZ 000500	152 MT	20.412 KG	NONE		1 RG59 + 2C18 SH + 2C18

Revision Number: 1 Revision Date: 07-15-2008

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.