

METRIC MEASUREMENT VERSION

5284UE Composite - CCTV and PTZ Applications

For more Information
please call

1-800-Belden1



Description:

23 AWG solid BC conductors, polyolefin insulation, plus 2 power conductors, 16 AWG stranded (19x29) tinned copper conductors, polypropylene insulation, unshielded, overall F-R PVC jacket.

Usage (Overall)

Suitable Applications: UTP-CCTV, CCTV Video/Control, Surveillance, Video Over Twisted Pairs, Closed Circuit Television

Twisted Pair

Physical Characteristics

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material | Dia. (mm) |
|---------|-----|-----------|--------------------|-----------|
| 2 | 23 | Solid | BC - Bare Copper | 0.584 |

Insulation

Insulation Material:

| Insulation Material | Dia. (mm) |
|---------------------|-----------|
| PO - Polyolefin | 1.016 |

Twisted Pair Color Code Chart:

| Number | Color |
|--------|-------------------------|
| 1 | Blue and White/Blue |
| 2 | Orange and White/Orange |

Inner Shield

Inner Shield Material:

| Inner Shield Material |
|-----------------------|
| Unshielded |

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

| Capacitance (pF/m) |
|--------------------|
| 49.215 |

Maximum Capacitance Unbalance:

| Capacitance (pF/m) |
|--------------------|
| 1082.730 |

Nominal Velocity of Propagation:

| VP (%) |
|--------|
| 70.000 |

Maximum Delay:

| Delay (ns/m) |
|--------------|
| 147.645 |

Maximum Conductor DC Resistance:

| DCR @ 20°C (Ohm/100 m) |
|------------------------|
| 9.000 |

Maximum DCR Unbalanced:

| DCR Unbalance @ 20°C (%) |
|--------------------------|
| |

5.000

Premise Cable Electricals:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. PSNEXT (dB) | Fitted Imp. (Ohms) |
|-------------|-----------------------------|------------------|--------------------|
| 1.0 | 2.000 | 62 | 100 ± 15% |
| 4.0 | 4.100 | 53 | 100 ± 15% |
| 8.0 | 5.800 | 48 | 100 ± 15% |
| 10.0 | 6.500 | 47 | 100 ± 15% |
| 16.0 | 8.200 | 44 | 100 ± 15% |
| 20.0 | 9.300 | 42 | 100 ± 15% |
| 25.0 | 10.400 | 41 | 100 ± 15% |
| 31.25 | 11.700 | 39 | 100 ± 15% |
| 62.5 | 17.000 | 35 | 100 ± 15% |
| 100 | 22.000 | 32 | 100 ± 15% |

Premise Cable Electrical Table 1:

| Freq. (MHz) | Min. PSACR (dB) | Min RL (dB) |
|-------------|-----------------|-------------|
| 1 | 60 | 20.000 |
| 4 | 49 | 23.000 |
| 8 | 43 | 24.500 |
| 10 | 41 | 25.000 |
| 16 | 36 | 25.000 |
| 20 | 34 | 25.000 |
| 25 | 31 | 24.300 |
| 31.25 | 28 | 23.600 |
| 62.5 | 19 | 21.500 |
| 100 | 11 | 20.100 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Min. PSELFEXT (dB) |
|-------------|--------------------|
| 1 | 61 |
| 4 | 49 |
| 8 | 43 |
| 10 | 41 |
| 16 | 37 |
| 20 | 35 |
| 25 | 33 |
| 31.25 | 31 |
| 62.5 | 24 |
| 100 | 21 |

Multi Conductor

Physical Characteristics

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------------|-----|-----------|--------------------|-----------|
| 2 | 16 | 19x29 | TC - Tinned Copper | 1.499 |

Insulation

Insulation Material:

| Insulation Material | Dia. (mm) |
|---------------------|-----------|
| PP - Polypropylene | 1.956 |

Insulation Color Code Chart:

| Number | Color |
|--------|-------|
| 1 | Red |
| 2 | Black |

Individual Shield

Electrical Characteristics

Maximum Conductor DC Resistance:

| DCR @ 20°C (Ohm/100 m) |
|------------------------|
| 1.470 |

Physical Characteristics (Overall)

Conductor

Outer Shield

Outer Shield Material:

Outer Shield Material

Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material

F-R PVC - Flame Retardant Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 5.918 mm

Mechanical Characteristics (Overall)

Bulk Cable Weight: 47.622 Kg/Km

Max. Recommended Pulling Tension: 467.061 N

Min. Bend Radius/Minor Axis: 50.800 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Other Standards: ISO/IEC 11801, Category 5e for data pair

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: UL1666 Riser

C(UL) Flame Test: FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 6284UE

Electrical Characteristics (Overall)

Max. Operating Voltage - Non-UL:

Voltage

300 V RMS

Notes (Overall)

Notes: Overall jacket sequentially marked.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|--------|-------------|-------|-------|-------------------------|
| 5284UE 0091000 | 305 MT | 19.958 KG | WHITE | C | 2 PR #23 + 2 #16 PP PVC |

METRIC MEASUREMENT VERSION

5284UE Composite - CCTV and PTZ Applications

| | | | | | |
|----------------|--------|-----------|-------|---|-------------------------|
| 5284UE 009500 | 152 MT | 10.206 KG | WHITE | C | 2 PR #23 + 2 #16 PP PVC |
| 5284UE 0101000 | 305 MT | 19.958 KG | BLACK | C | 2 PR #23 + 2 #16 PP PVC |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-23-2010

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.